#### **PRODUCT DATA**



# FASSON® Clear PET DI-OF

Issued July 2024

#### Introduction

Qualified self-adhesive material for INDIGO DIGITAL presses. Optimised to secure excellent runability and print performance.

Description

Face: A clear transparent polyester film, glossy finish.

Availability

	Adhesive 🗢	Permanent
Backing <b>U</b>		
No cracklines		x

## **Printing & Conversion**

This product is specifically engineered for use on the INDIGO DIGITAL sheet-fed press The face material gives excellent toner key (no pre-treatment needed). Stable construction ensures problem-free runability. Before applying the label, the surface must be clean, dry, and grease-free.

**Features:** Authorised material ensures problem free conversion.

#### Recommendations for use

Multi-colour quality labels, window-and internal illuminated sign stickers using the advantages of full-colour DIGITAL printing such as: short runs, personalization etc. For indoor and outdoor use.

#### General

Shelf life: 2 years stored at 20°C / 55% R.H.

Total caliper (±10 %): 229 micron

For information regarding EHS regulation, please visit our website under downloads "Technical bulletins" TB 7.8 Product Compliance Fasson Offset" and for technical guidance "Technical bulletins" – Offset printing.



#### **PRODUCT CHARACTERISTICS**

### **Physical properties**

#### **Face**

Basis weight:105 g/m²ISO 536Caliper:76 micronISO 534

#### **Adhesive**

Permanent: A glass clear, acrylic-based adhesive for maximum sunlight and weather

resistance. Good initial tack and ultimate adhesion.

Adhesion (N/25mm)

(FTM 1 on steel/20 min. bond time) 15.4

Tack(N)

(FTM 9 on st.steel) 10.3 Minimum application temperature +5

Service temperature range

after 24 hrs (°C) +80

Resistance to cold (°C)<sup>1)</sup> down to -20

### **Backing**

No cracklines: A bleached one-side-coated white kraft, especially designed for sheet products,

featuring minimal moisture sensitivity.

Basis weight: 120 g/m<sup>2</sup> ISO 536 Caliper: 118 micron ISO 534

#### Guarantee and liability:

Guarantee and inabinity:

All products statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see https://www.lecta.com/terms
Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel – Lecta under license from Avery Dennison Corporation and related entities for EMENA only.



<sup>1)</sup> Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.