

PRODUCT DATA

FASSON®

FASSON® Crack-Back® Plus Copyface FSC® Certified

Issued May 2021

Introduction

A self-adhesive paper sheet product for offset printing combined with the unique, diagonal Crack-Back® Plus backing removal system.

Description

Face: A white woodfree printing paper with a special self-copying coating, featuring an image-forming reaction with carbonless papers, designed to provide a self-adhesive label as the last part in a multi-part CB/CF-coated form set.
This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Availability	Adhesive ➡	Permanent
Backing ⤴		
Crack-Back® Plus (diagonal cracklines)		x

Printing & Conversion

Offset printing.
Before applying the label, the surface must be clean, dry and grease-free.

Features: Excellent lay flatness, enabling high-speed printing.
The unique Crack-Back Plus backing removal system with diagonal scored lines facilitates creating layouts, conversion and application of the label.

Uses: Form sets, used in conjunction with order CB/CBF-papers.
Hospital labeling order picking-, shipping-, inventory labels: on flat or curved surfaces.
For indoor use only.

General

Shelf life: 2 years stored at 20°C / 55% R.H.
Total caliper (±10 %): 171 micron

For information regarding EHS regulation, please visit our website under downloads “Technical bulletins“ TB 7.8 Product Compliance Fasson Offset” and for technical guidance “Technical bulletins“ – Offset printing.

PRODUCT CHARACTERISTICS

Physical properties

Face

Basis weight:	80 g/m ²	ISO 536
Caliper:	100 micron	ISO 534
Tensile:	5.2 kN/m MD	ISO 1924/2
Tear (Elmendorf):	440 mN MD	ISO 1974
Opacity:	85 %	ISO 2471

Adhesive

Permanent: General-purpose emulsion-based permanent adhesive with a high initial tack and high adhesion on most common substrates.

Permanent

Adhesion (N/m) (FTM 2 on steel/20 min. bond time)	365
Tack (N/m) (FTM9 on glass)	380
Minimum application temperature	> +5
Service temperature range up to 24 hrs (°C)	+80
up to 1 hr (°C)	+110
Resistance to cold (°C) ¹⁾ down to	-40

¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.

Backing

Crack-Back® Plus: One-side-coated bleached kraft paper, with diagonally crush-scored lines, along which the backing will crack cleanly when bent back, allowing easy removal in just two pieces. Lines are spaced just 32 mm apart. Good lay flatness ensures first-class printing and finishing. *(For optimal functionality take care of the following: minimum label size must be 20 cm². The shortest side of a rectangle or the smallest diameter of an ellipse must be at least 25 mm.)*

Basis weight:	86 g/m ²	ISO 536
Caliper:	87 micron	ISO 534

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>
Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.