

PRODUCT DATA

FASSON®

FASSON® Offset Vinyl

Issued August 2021

Introduction

A self-adhesive film sheet product for offset printing.

Description

Face: Soft vinyl film, specially formulated for offset printing.
Available in gloss and matt white and in gloss and matt transparent.

Availability	Adhesive ➡	Permanent	Removable
<i>Backing</i> ⤴			
No cracklines		x	x

Printing & Conversion

Offset printing: with both purely oxidative drying and UV-curing inks, which are resistant to plasticizer /suitable for films.

Screen-printing: with conventional (i.e. solvent-based) and UV-curing inks. Consult your printing ink supplier about suitable printing inks. All printing inks should be tested for suitability prior to use.

Advanced ink technology, and the ink-receptive surface of Offset Vinyl, ensures successful printing if the recommendations are followed.

Before applying the label, the surface must be clean, dry and grease-free.

Features: Excellent lay-flatness, enabling high-speed printing
Ability to create fine halftone prints.
Accurate register.

Recommendations for use: Promotional stickers, point-of-sale material, short-term outdoor markings.
Outdoor durability up to 2 years.

General

Shelf life: 1 years stored at 20°C / 55% R.H.
Total caliper (±10 %): 235 micron

For information regarding EHS regulation, please visit our website under downloads “Technical bulletins“ TB 7.8 Product Compliance Fasson Offset” and for technical guidance “Technical bulletins“ – Offset printing.

PRODUCT CHARACTERISTICS

Physical properties

Face	White gloss/matt	Transparent gloss/matt		
Basis weight:	112/113	110/113	g/m ²	ISO 536
Caliper:	80	80	micron	ISO 534
Gloss 20°/85°:	70/20	n.a.	%	DIN 67530
Opacity:	94/91	n.a.	%	ISO 2471

Adhesive

Permanent: Clear acrylic adhesive featuring excellent UV and weather resistance.
 Removable: Clear acrylic adhesive featuring excellent UV and weather resistance.
Caution: Removability can be inhibited if the label is applied to surfaces with which it could react, such as surfaces printed with nitro-cellulose paints, ABS, polystyrenes, screen-printing inks (fresh), certain types of PVC.

	Permanent	Removable
Adhesion (N/m) (FTM 1 on steel/after 24h)	800	200
Tack (N/m) (FTM 9 on glass)	280	200
Minimum application temperature	> +5	> +10
Service temperature range up to 24 hrs (°C)	+80	+80
up to 1 hr (°C)	+110	+110
Resistance to cold (°C) ¹⁾ down to	-40	-20

¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.

Backing

No cracklines: A bleached one side-coated white kraft, especially designed for sheet products, featuring minimal moisture sensitivity.

Basis weight:	128 g/m ²	ISO 536
Caliper:	132 micron	ISO 534

Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>

Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.